Czech ODN Passive Devices



Overview

Passive automatic search, detection and tracking functions are key elements in silent operations or tactical scenarios saturated with enemy jamming, such as Ukraine.

Key Takeaways

Czech ODN passive devices, such as splitters, couplers, and WDM modules, are designed for low insertion loss, high stability, and minimal noise in fiber-optic networks.

Overview of ODN Passive Devices

In a Passive Optical Network (PON), the Optical Distribution Network (ODN) connects the Optical Line Terminal (OLT) to multiple Optical Network Units (ONUs) or Terminals (ONTs) using unpowered devices. The key passive components include: Optical Splitters: Divide a single optical signal into multiple outputs (e.g., 1: 2, 1: 4, 1: 32) while maintaining low insertion loss and high directivity. Fused Couplers: Provide stable multi-port signal splitting with low polarization-dependent loss (PDL) and minimal total dispersion loss (TDL), ensuring low-noise operation.

Wavelength Division Multiplexers (WDM): Combine or separate multiple wavelengths for efficient fiber utilization, including CWDM and DWDM modules. Attenuators: Mechanical or fixed/variable devices that reduce optical power to prevent equipment overload, designed with low insertion loss and high repeatability. Polarization Maintaining (PM) Components: Include PM splitters, combiners, and isolators to preserve signal integrity and reduce noise in sensitive applications.

© 2026 ENSAA OPTICAL NETWORKS - All rights reserved

Key Performance Features

Czech passive devices, such as those from SENKO, emphasize low-noise characteristics through: Low Insertion Loss: Typically ≤1. 2 dB for 1x2 couplers, ensuring minimal signal degradation. High Return Loss: ≥55 dB, reducing back-reflection and interference in the network.

Low Polarization-

Dependent Loss (PDL): ≤0. 15 dB, maintaining signal quality across polarization states. Temperature Stability: Operating range from -40°C to +85°C, ensuring consistent performance in outdoor ODN deployments.

Compact and Robust Packaging: Options include 900 µm tubes, 2 mm/3 mm tubes, or ABS boxes for easy installation and protection.

Applications

These low-noise passive devices are suitable for: FTTx Deployments: Fiber-to-the-Home (FTTH) or Fiber-to-the-Premises (FTTP) networks. Telecommunications and Broadband Access: Supporting GPON, EPON, NG-PON2, and XGS-PON architectures. Network Monitoring and Testing: Ensuring accurate signal distribution and minimal interference in optical test setups.

High-

Density Splitter Modules: Pre-connectorized PLC splitters for rapid deployment and reduced operational costs.

Summary

Czech OD

N passive devices combine high reliability, low insertion loss, and low-noise performance to optimize optical network efficiency. Their design supports modern PON architectures, enabling high-speed, low-latency, and stable fiber-optic communication while minimizing signal degradation and noise across the network.

© 2026 ENSAA OPTICAL NETWORKS - All rights reserved

Article Content

System DPET: All-seeing eye of the Army of the Czech

The term passive reflects the fact that the system does not emit any signals during its operation, making it invisible to electromagnetic warfare assets on the

IRST Pods: Eagle Eyes for Passive Detection

Passive automatic search, detection and tracking functions are key elements in silent operations or tactical scenarios saturated with enemy jamming, such as Ukraine. This article focuses

Low Noise ODN Passive Devices for Wind Power Generation

Communication Network Architectures Based on Wind power Noise Reduction Technologies for Turbines: A Design and Testing of Passive Filters for Acoustic Noise Mitigation in Noise Reduction

Czech AI startup detects drones via sound at €150 per sensor, targets ...

The system offers a passive, low-cost alternative to radar for detecting low-flying drones over urban areas, critical infrastructure, and military sites. For the past decade, the company has

iC-OD Series

The iC-OD/L device is an optical position sensitive detector with a monolithic integrated photodiode. filter. A lowpass filter reduces high-frequency interference to a minimum. The maximum sensitivity for

DIGITIZATION OF OPTICAL DISTRIBUTION NETWORKS (ODN)

In October 2022 it announced a new product set called Light ODN which uses pre-connectorized splitters, distribution frames, drop cables, and other devices to enable zero splice, plug-and-play

AVX Czech Republic s.r.o.

Passive component manufacturer. AVX Czech Republic s.r.o. is a major producer of tantalum and niobium SMD capacitors. Tomas Zednicek was awarded a master degree in Electrotechnology by

The Sound Shield Drone Acoustic Shield Was

The Sound Shield system is based on fully passive sensors that do not emit any signals. Therefore, the enemy cannot detect them or disable them

Adapter-Passive Devices-Grandway

© 2026 ENSAA OPTICAL NETWORKS - All rights reserved

Features 1.Low insertion loss. 2.Guaranteed repeatablity and high reliability. 3.ZrO2 sleeve. 4.FC,SC,LC,ST etc. Adapters are available. 5.Simplex,Duplex or Quad type.

Chapter 10 Passive Devices

nuation as low as 0.1 dB). These small losses are mostly induced by a mismatch of the fibre core parameters (numerical aperture, diameter) or a lateral and angular misalignment, and the energy that

Optimized passive devices for low-power LNA design

This paper addresses the design of high-Q passive inductors and differential transformers in a low-power low-noise amplifier (LNA) application. The passives quality in resonant LC tanks as

Passive optical network

A passive optical network (PON) is a fiber-optic telecommunications network that uses only unpowered devices to carry signals, as opposed to electronic equipment.

Passive Mixers Increase Gain and Decrease Noise

The LTC554x family of passive downconverting mixers covers frequencies from 600MHz to 4GHz and delivers high conversion gain and low

Optical Amplifiers for Access and Passive Optical Networks: A ...

For many years, passive optical networks (PONs) have received a considerable amount of attention regarding their potential for providing broadband connectivity, especially in remote areas,

Low Noise ODN Passive Devices for Wind Power Generation

Holistic approach to wind turbine noise: From blade trailing-edge Low-Noise Technologies for Wind Turbine Blades Power electronics in wind generation systems A review of common-mode voltage

Understanding the Difference Between Active and Passive Noise

Discover the difference between active and passive noise cancellation. Learn how each works, their benefits, and which is best for your needs in noisy environments.

2.1 dB noise figure 5.2 GHz CMOS low noise amplifier using wafer

This work presents an inductor with a high quality factor (Q) that is fabricated using wafer-level integrated passive device (IPD) technology and a 5.2 GHz differential low noise amplifier

AVX Czech Republic s.r.o.

© 2026 ENSAA OPTICAL NETWORKS - All rights reserved

Passive component manufacturer. AVX Czech Republic s.r.o. is a major producer of tantalum and niobium SMD capacitors. Noise measurement of capacitors (prof.Sikula) Capacitor characteristation

Contact Us

Continue your research online:

Website: https://ensaa.es
Technical inquiry: https://ensaa.es/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 ENSAA OPTICAL NETWORKS - All rights reserved